

DISTANCE ULTRA EFFICIENCY 96

Linear strip high efficiency CRI96 up to 35m one end powered
Ruban LED haute efficacité IRC96 de longueur jusqu'à 35m
A4128



Temperature de couleur CCT

1800K - 2100K - 2300K - 2700K - 3000K - 3500K - 4000K - 5000K - 6000K - 6500K

Precision de couleur & IRC Color consistency & CRI OneBinOnly | >96

Rendement lumineux Luminous Efficacy (@4000K) 105 lm/w

Puissance & nombre de led Power & number of Led 10 w/m & 140 leds/m


Coupe Cutting unit 100 mm

Dimensions Dimensions 35000 x 10 x 1,2 mm


Tension d'alimentation & Classe isolation Input voltage & Class 48 Vdc | class III

Température d'utilisation Ambient temperature - 10°C / + 40°C

10w



Cutting unit



A4128.10.140.930.IP20.DALI

Power & number leds/m

10 w/m & 140 leds/m

Custom power on request (5 to 15W)

CCT & luminous flux/m

1800K	800 lm	918
2100K	850 lm	921
2300K	900 lm	923
2700K	950 lm	927
3000K	1000 lm	930
3500K	1000 lm	935
4000K	1050 lm	940
5000K	1050 lm	950
6000K	1050 lm	960
6500K	1050 lm	965

IP Rating

IP20

IP54 (Wet indoor)

IP65H (semi indoor)

Pour des IP supérieur, veuillez nous consulter
For higher IP ratings, please contact us.

Dimming

No dimming

Dali

Dmx

Dimming 0/1-10V

Casambi

10.140

IP20

IP54

IP65H

HF

DALI

DMX

D10

CSB